

40

AGB series

40X40X20mm

●General Specification / 一般規格

- Motor / DC brushless motor
- Material / Frame : plastic(94V-0)
- Impeller : plastic(94V-0)
- Bearing / Ball bearing
- Weight / 45g
- 馬達 / 直流單向無刷馬達
- 材質 / 框：塑膠(94V-0)
- 葉：塑膠(94V-0)
- 軸承 / 滾珠軸承
- 重量 / 45g



●Specification / 詳細規格 * 軸承/bearing B: 雙滾珠/ball bearing F:FMB S: 含油軸承/sleeve bearing

Model	Bearing	Voltage	Operating Vol.	Current	Speed	Max. Air Flow	Max. Static Pressure	Sound	P-Q		
機型	軸承	電壓	操作電壓	電流	轉速	最大風量	最大風壓	噪音	P-Q曲線		
P/N	B / S / F	V	V	A	RPM	m ³ /min	CFM	Pa	In-H ₂ O	dBA	No.
AGB04020_12L	B	12	7.0~13.2	0.08	8000	0.27	9.4	87.4	0.35	33	①
AGB04020_12M	B	12	7.0~13.2	0.11	10000	0.33	11.7	136.9	0.55	40	②
AGB04020_12H	B	12	7.0~13.2	0.17	12000	0.41	14.3	196.7	0.79	44	③
AGB04020_12U	B	12	7.0~13.2	0.25	14000	0.48	16.8	268.0	1.08	49	④
AGB04020_12V	B	12	7.0~13.2	0.41	16000	0.56	19.8	358.3	1.44	53	⑤
AGB04020_24H	B	24	14.0~26.4	0.13	12000	0.41	14.3	196.7	0.79	44	③
AGB04020_24U	B	24	14.0~26.4	0.15	14000	0.48	16.8	268.0	1.08	49	④
AGB04020_24V	B	24	14.0~26.4	0.18	16000	0.56	19.8	358.3	1.44	53	⑤

● Drawing & panel out-cuts/ 圖面及出入風口

● Characteristic Curves/ 特性曲線

