

# 40

## AGB series

### 40X40X28mm

#### ●General Specification / 一般規格

- Motor / DC brushless motor
- Material / Frame : plastic(94V-0)  
Impeller : plastic(94V-0)
- Bearing / Ball bearing
- Weight / 58g
- 馬達 / 直流單向無刷馬達
- 材質 / 框：塑膠(94V-0)  
葉：塑膠(94V-0)
- 軸承 / 滾珠軸承
- 重量 / 58克



#### ●Specification / 詳細規格 \* 軸承/bearing B: 雙滾珠/ball bearing F:FMB S: 含油承軸/sleeve bearing

Model 機型	Bearing 軸承	Voltage 電壓	Operating Vol. 操作電壓	Current 電流	Speed 轉速	Max. Air Flow 最大風量		Max. Static Pressure 最大風壓		Sound 噪音	P-Q P-Q曲線
P/N	B / S / F	V	V	A	RPM	m <sup>3</sup> /min	CFM	Pa	In-H <sub>2</sub> O	dBA	No.
AGB04028_12L	B	12	7.0~13.2	0.14	8000	0.40	13.8	114.5	0.46	38	①
AGB04028_12M	B	12	7.0~13.2	0.26	9500	0.45	15.9	171.8	0.69	44	②
AGB04028_12H	B	12	7.0~13.2	0.35	11000	0.53	18.7	229.1	0.92	51	③
AGB04028_12U	B	12	7.0~13.2	0.55	13000	0.67	23.8	328.7	1.32	54	④
AGB04028_12V	B	12	7.0~13.2	0.64	15000	0.70	24.8	407.9	1.64	58	⑤
AGB04028_24L	B	24	14.0~26.4	0.10	8000	0.40	13.8	114.5	0.46	38	①
AGB04028_24M	B	24	14.0~26.4	0.15	9500	0.45	15.9	171.8	0.69	44	②
AGB04028_24H	B	24	14.0~26.4	0.20	11000	0.53	18.7	229.1	0.92	51	③
AGB04028_24U	B	24	14.0~26.4	0.27	13000	0.67	23.8	328.7	1.32	54	④

