

50

AGE series

50X50X10mm

●General Specification / 一般規格

- Motor / DC brushless motor
- Material / Frame : plastic(94V-0)
Impeller : plastic(94V-0)
- Bearing / Ball bearing;FMB
- Weight / 32g
- 馬達 / 直流單向無刷馬達
- 材質 / 框：塑膠(94V-0)
葉：塑膠(94V-0)
- 軸承 / 滾珠軸承;FMB
- 重量 / 32克



●Specification / 詳細規格 * 軸承/bearing B: 雙滾珠/ball bearing F:FMB S: 含油軸承/sleeve bearing

Model 機型	Bearing 軸承	Voltage 電壓	Operating Vol. 操作電壓	Current 電流	Speed 轉速	Max. Air Flow 最大風量	Max. Static Pressure 最大風壓	Sound 噪音	P-Q P-Q曲線
P/N	B / S / F	V	V	A	RPM	m ³ /min CFM	Pa In-H ₂ O	dBA	No.
AGE05010_05J	B / F	5	4.5~5.5	0.08	3500	0.19 6.7	12.5 0.05	18	①
AGE05010_05L	B / F	5	4.5~5.5	0.12	4500	0.23 8.2	22.4 0.09	25	②
AGE05010_05M	B / F	5	4.5~5.5	0.16	5500	0.30 10.5	34.9 0.14	30	③
AGE05010_05H	B / F	5	4.5~5.5	0.20	6500	0.36 12.7	44.8 0.18	35	④
AGE05010_12J	B / F	12	7.0~13.2	0.05	3500	0.19 6.7	12.5 0.05	18	①
AGE05010_12L	B / F	12	7.0~13.2	0.07	4500	0.23 8.2	22.4 0.09	25	②
AGE05010_12M	B / F	12	7.0~13.2	0.08	5500	0.30 10.5	34.9 0.14	30	③
AGE05010_12H	B / F	12	7.0~13.2	0.10	6500	0.36 12.7	44.8 0.18	35	④
AGE05010_24J	B / F	24	14.0~26.4	0.06	3500	0.19 6.7	12.5 0.05	18	①
AGE05010_24L	B / F	24	14.0~26.4	0.07	4500	0.23 8.2	22.4 0.09	25	②
AGE05010_24M	B / F	24	14.0~26.4	0.08	5500	0.30 10.5	34.9 0.14	30	③
AGE05010_24H	B / F	24	14.0~26.4	0.09	6500	0.36 12.7	44.8 0.18	35	④

● Drawing & panel out-cuts/ 圖面及出入風口

● Characteristic Curves/ 特性曲線

