

50

AGC series

50X50X15mm

●General Specification / 一般規格

- Motor / DC brushless motor
- Material / Frame : plastic(94V-0)
- Impeller : plastic(94V-0)
- Bearing / Ball bearing;FMB
- Weight / 38g
- 馬達 / 直流單向無刷馬達
- 材質 / 框：塑膠(94V-0)
- 葉：塑膠(94V-0)
- 軸承 / 滾珠軸承;FMB
- 重量 / 38克



●Specification / 詳細規格 * 軸承/bearing B: 雙滾珠/ball bearing F:FMB S: 含油軸承/sleeve bearing

Model 機型	Bearing 軸承	Voltage 電壓	Operating Vol. 操作電壓	Current 電流	Speed 轉速	Max. Air Flow 最大風量		Max. Static Pressure 最大風壓		Sound 噪音	P-Q P-Q曲線
P/N	B / S / F	V	V	A	RPM	m ³ /min	CFM	Pa	In-H ₂ O	dBA	No.
AGC05015_12J	B / F	12	7.0~13.2	0.06	3600	0.28	9.91	20.9	0.08	24	①
AGC05015_12L	B / F	12	7.0~13.2	0.07	4200	0.39	12.2	28.9	0.12	27	②
AGC05015_12M	B / F	12	7.0~13.2	0.09	4800	0.37	13.2	38.6	0.16	30	③
AGC05015_12H	B / F	12	7.0~13.2	0.11	5400	0.42	15.0	45.8	0.18	32	④
AGC05015_12U	B / F	12	7.0~13.2	0.13	6000	0.48	17.0	57.3	0.23	36	④
AGC05015_24J	B / F	24	14.0~26.4	0.04	3600	0.28	9.91	20.9	0.08	24	①
AGC05015_24L	B / F	24	14.0~26.4	0.05	4200	0.39	12.2	28.9	0.12	27	②
AGC05015_24M	B / F	24	14.0~26.4	0.06	4800	0.37	13.2	38.6	0.16	30	③
AGC05015_24H	B / F	24	14.0~26.4	0.07	5400	0.42	15.0	45.8	0.18	32	④
AGC05015_24U	B / F	24	14.0~26.4	0.08	6000	0.48	17.0	57.3	0.23	36	⑤

● Drawing & panel out-cuts/ 圖面及出入風口

● Characteristic Curves/ 特性曲線

