

70

AGE series

70X70X25mm

●General Specification / 一般規格

- Motor / DC brushless motor
- Material / Frame : plastic(94V-0)
Impeller : plastic(94V-0)
- Bearing / Ball bearing;sleeve bearing
- Weight / 74g
- 馬達 / 直流單向無刷馬達
- 材質 / 框：塑膠(94V-0)
葉：塑膠(94V-0)
- 軸承 / 滾珠軸承;含油軸承
- 重量 / 74克



●Specification / 詳細規格 * 軸承/bearing B: 雙滾珠/ball bearing F:FMB S: 含油軸承/sleeve bearing

Model 機型	Bearing 軸承	Voltage 電壓	Operating Vol. 操作電壓	Current 電流	Speed 轉速	Max. Air Flow 最大風量	Max. Static Pressure 最大風壓	Sound 噪音	P-Q P-Q曲線
P/N	B / S / F	V	V	A	RPM	m ³ /min CFM	Pa In-H ₂ O	dBA	No.
AGE07025_12L	B / S	12	7.0~13.2	0.07	3000	0.85 30.0	37.4 0.15	27	①
AGE07025_12M	B / S	12	7.0~13.2	0.09	3600	1.02 35.6	54.8 0.22	32	②
AGE07025_12H	B / S	12	7.0~13.2	0.13	4000	1.13 39.9	67.2 0.27	37	③
AGE07025_12U	B	12	7.0~13.2	0.16	5500	1.55 54.8	124.5 0.50	45	④
AGE07025_24L	B / S	24	14.0~26.4	0.05	3000	0.85 30.0	37.4 0.15	27	①
AGE07025_24M	B / S	24	14.0~26.4	0.06	3600	1.02 35.6	54.8 0.22	32	②
AGE07025_24H	B / S	24	14.0~26.4	0.08	4000	1.13 39.9	67.2 0.27	37	③
AGE07025_24U	B	24	14.0~26.4	0.35	5500	1.55 54.8	124.5 0.50	45	④
AGE07025_48L	B / S	48	28.0~56.0	0.04	3000	0.85 30.0	37.4 0.15	27	①
AGE07025_48M	B / S	48	28.0~56.0	0.05	3600	1.02 35.6	54.8 0.22	32	②
AGE07025_48H	B / S	48	28.0~56.0	0.07	4000	1.13 39.9	67.2 0.27	37	③

● Drawing & panel out-cuts/ 圖面及出入風口

● Characteristic Curves/ 特性曲線

