

80

AGE series

80X80X25mm



General Specification / 一般規格

- Motor / DC brushless motor
- Material / Frame : plastic(94V-0)
Impeller : plastic(94V-0)
- Bearing / Ball bearing;FMB;sleeve bearing
- Weight / 80g
- 馬達 / 直流單向無刷馬達
- 材質 / 框：塑膠(94V-0)
葉：塑膠(94V-0)
- 軸承 / 滾珠軸承;FMB;含油軸承
- 重量 / 80克

Specification / 詳細規格 * 軸承/bearing B: 雙滾珠/ball bearing F:FMB S: 含油軸承/sleeve bearing

Model 機型	Bearing 軸承	Voltage 電壓	Operating Vol. 操作電壓	Current 電流	Speed 轉速	Max. Air Flow 最大風量	Max. Static Pressure 最大風壓	Sound 噪音	P-Q P-Q曲線		
P/N	B / S / F	V	V	A	RPM	m³/min	Pa	In-H ₂ O	No.		
AGE08025_05U	B / F / S	5	4.5~5.5	0.30	2700	0.90	31.8	28.4	0.11	28	①
AGE08025_12J	B / F / S	12	7.0~13.2	0.17	2700	0.90	31.8	28.4	0.11	29	①
AGE08025_12L	B / F / S	12	7.0~13.2	0.19	3000	1.00	35.4	35.3	0.14	33	②
AGE08025_12M	B / F / S	12	7.0~13.2	0.23	3600	1.20	42.4	49.0	0.20	38	③
AGE08025_12H	B / F / S	12	7.0~13.2	0.32	4300	1.43	50.5	66.7	0.27	43	④
AGE08025_12U	B / F	12	7.0~13.2	0.50	5000	1.69	60.0	94.1	0.38	48	⑤
AGE08025_12V	B	12	7.0~13.2	0.50	5700	2.10	74.3	94.1	0.38	50	⑥
AGE08025_24J	B / F / S	24	14.0~26.4	0.08	2700	0.90	31.8	28.4	0.11	29	①
AGE08025_24L	B / F / S	24	14.0~26.4	0.11	3000	1.00	35.4	35.3	0.14	33	②
AGE08025_24M	B / F / S	24	14.0~26.4	0.16	3600	1.20	42.4	49.0	0.20	38	③
AGE08025_24H	B / F / S	24	14.0~26.4	0.23	4300	1.43	50.5	66.7	0.27	43	④
AGE08025_24U	B	24	4.0~26.4	0.25	5000	1.69	60.0	94.1	0.38	48	⑤
AGE08025_48M	B / F / S	48	28.0~56.0	0.06	3000	1.00	35.4	35.3	0.14	33	②
AGE08025_48H	B / F / S	48	28.0~56.0	0.09	3600	1.20	42.4	49.0	0.20	38	③
AGE08025_48U	B / F / S	48	28.0~56.0	0.20	4300	1.43	50.5	66.7	0.27	43	④
AGE08025_48V	B	48	28.0~56.0	0.21	5000	1.69	60.0	94.1	0.38	48	⑤

Drawing & panel out-cuts/ 圖面及出入風口

Characteristic Curves/ 特性曲線

