

80

AGC series

80X80X25mm

●General Specification / 一般規格

- Motor / DC brushless motor
- Material / Frame : plastic(94V-0)
Impeller : plastic(94V-0)
- Bearing / Ball bearing;FMB
- Weight / 85g
- 馬達 / 直流單向無刷馬達
- 材質 / 框：塑膠(94V-0)
葉：塑膠(94V-0)
- 軸承 / 滾珠軸承;FMB
- 重量 / 85克



●Specification / 詳細規格 * 軸承/bearing B: 雙滾珠/ball bearing F:FMB S: 含油軸承/sleeve bearing

Model 機型	Bearing 軸承	Voltage 電壓	Operating Vol. 操作電壓	Current 電流	Speed 轉速	Max. Air Flow 最大風量	Max. Static Pressure 最大風壓	Sound 噪音	P-Q
P/N	B / S / F	V	V	A	RPM	m ³ /min CFM	Pa In-H ₂ O	dBA	No.
AGC08025_12L	B / F	12	7.0~13.2	0.14	2700	0.98 34.6	29.9 0.12	28	①
AGC08025_12M	B / F	12	7.0~13.2	0.20	3000	1.09 38.5	42.3 0.17	31	②
AGC08025_12H	B / F	12	7.0~13.2	0.24	3600	1.54 54.3	69.7 0.28	36	③
AGC08025_12U	B / F	12	7.0~13.2	0.44	4300	1.73 61.2	79.7 0.32	40	④
AGC08025_24J	B / F	24	14.0~26.4	0.08	2700	0.98 34.6	29.9 0.12	28	①
AGC08025_24L	B / F	24	14.0~26.4	0.11	3000	1.09 38.5	42.3 0.17	31	②
AGC08025_24M	B / F	24	14.0~26.4	0.20	3600	1.54 54.3	69.7 0.28	36	③
AGC08025_24H	B / F	24	14.0~26.4	0.20	4300	1.73 61.2	79.7 0.32	40	④
AGC08025_48J	B / F	48	28.0~56.0	0.05	2700	0.98 34.6	29.9 0.12	28	①
AGC08025_48L	B / F	48	28.0~56.0	0.07	3000	1.09 38.5	42.3 0.17	31	②
AGC08025_48M	B / F	48	28.0~56.0	0.07	3600	1.54 54.3	69.7 0.28	36	③
AGC08025_48H	B / F	48	28.0~56.0	0.11	4300	1.73 61.2	79.7 0.32	40	④

● Drawing & panel out-cuts/ 圖面及出入風口

● Characteristic Curves/ 特性曲線

