

# 80

## AGB series

### 80X80X38mm

#### ●General Specification / 一般規格

- Motor / DC brushless motor
- Material / Frame : plastic(94V-0)  
Impeller : plastic(94V-0)
- Bearing / Ball bearing
- Weight / 210g
- 馬達 / 直流單向無刷馬達
- 材質 / 框：塑膠(94V-0)  
葉：塑膠(94V-0)
- 軸承 / 滾珠軸承
- 重量 / 210克



#### ●Specification / 詳細規格 \* 軸承/bearing B: 雙滾珠/ball bearing F:FMB S: 含油軸承/sleeve bearing

Model 機型	Bearing 軸承	Voltage 電壓	Operating Vol. 操作電壓	Current 電流	Speed 轉速	Max. Air Flow 最大風量	Max. Static Pressure 最大風壓	Sound 噪音	P-Q P-Q曲線		
P/N	B / S / F	V	V	A	RPM	m³/min	CFM	Pa	In-H <sub>2</sub> O	dBA	No.
AGB08038_12L	B	12	7.0~13.2	0.40	4200	1.65	58.2	102.1	0.41	45	①
AGB08038_12M	B	12	7.0~13.2	0.76	5600	2.23	78.8	189.2	0.76	53	②
AGB08038_12H	B	12	7.0~13.2	1.00	6100	2.40	84.8	221.6	0.89	56	③
AGB08038_12U	B	12	7.0~13.2	1.50	7500	2.99	105.5	338.6	1.36	62	④
AGB08038_12V	B	12	7.0~13.2	2.70	9000	3.68	130.0	498.0	2.00	66	⑤
AGB08038_24L	B	24	14.0~26.4	0.25	4200	1.65	58.2	102.1	0.41	45	①
AGB08038_24M	B	24	14.0~26.4	0.35	5600	2.23	78.8	189.2	0.76	53	②
AGB08038_24H	B	24	14.0~26.4	0.45	6100	2.40	84.8	221.6	0.89	56	③
AGB08038_24U	B	24	14.0~26.4	0.82	7500	2.99	105.5	338.6	1.36	62	④
AGB08038_24V	B	24	14.0~26.4	1.40	9000	3.68	130.0	498.0	2.00	66	⑤
AGB08038_48L	B	48	28.0~56.0	0.23	4200	1.65	58.2	102.1	0.41	45	①
AGB08038_48M	B	48	28.0~56.0	0.33	5600	2.23	78.8	189.2	0.76	53	②
AGB08038_48H	B	48	28.0~56.0	0.51	6100	2.40	84.8	221.6	0.89	56	③
AGB08038_48U	B	48	28.0~56.0	0.58	7500	2.99	105.5	338.6	1.36	62	④
AGB08038_48V	B	48	28.0~56.0	0.90	9000	3.68	130.0	498.0	2.00	66	⑤

#### ● Drawing & panel out-cuts/ 圖面及出入風口

#### ● Characteristic Curves/ 特性曲線

