

92

AGE series

92X92X25mm

●General Specification / 一般規格

- Motor / DC brushless motor
- Material / Frame : plastic(94V-0)
Impeller : plastic(94V-0)
- Bearing / Ball bearing;FMB;sleeve bearing
- Weight / 85g
- 馬達 / 直流單向無刷馬達
- 材質 / 框：塑膠(94V-0)
葉：塑膠(94V-0)
- 軸承 / 滾珠軸承;FMB;含油軸承
- 重量 / 85克



●Specification / 詳細規格 * 軸承/bearing B: 雙滾珠/ball bearing F:FMB S: 含油軸承/sleeve bearing

| Model 機型 | Bearing 軸承 | Voltage 電壓 | Operating Vol. 操作電壓 | Current 電流 | Speed 轉速 | Max. Air Flow 最大風量 | Max. Static Pressure 最大風壓 | Sound 噪音 | P-Q P-Q曲線 |
|--------------|---------------|---------------|------------------------|---------------|-------------|----------------------------|------------------------------|-------------|--------------|
| P/N | B / S / F | V | V | A | RPM | m ³ /min CFM | Pa In-H ₂ O | dBA | No. |
| AGE09225_12J | B / F / S | 12 | 7.0~13.2 | 0.12 | 2100 | 1.05 37.0 | 23.4 0.09 | 25 | ① |
| AGE09225_12L | B / F / S | 12 | 7.0~13.2 | 0.14 | 2450 | 1.22 43.0 | 31.4 0.13 | 30 | ② |
| AGE09225_12M | B / F / S | 12 | 7.0~13.2 | 0.17 | 2850 | 1.35 47.5 | 41.6 0.17 | 34 | ③ |
| AGE09225_12H | B / F / S | 12 | 7.0~13.2 | 0.20 | 3200 | 1.61 56.8 | 57.5 0.23 | 38 | ④ |
| AGE09225_12U | B / F / S | 12 | 7.0~13.2 | 0.35 | 3800 | 1.81 64.0 | 64.4 0.26 | 45 | ⑤ |
| AGE09225_12V | B / F / S | 12 | 7.0~13.2 | 0.41 | 4200 | 2.16 76.1 | 87.5 0.35 | 49 | ⑥ |
| AGE09225_24J | B / F / S | 24 | 14.0~26.4 | 0.06 | 2100 | 1.05 37.0 | 23.4 0.09 | 25 | ① |
| AGE09225_24L | B / F / S | 24 | 14.0~26.4 | 0.08 | 2450 | 1.22 43.0 | 31.4 0.13 | 30 | ② |
| AGE09225_24M | B / F / S | 24 | 14.0~26.4 | 0.10 | 2850 | 1.35 47.5 | 41.6 0.17 | 34 | ③ |
| AGE09225_24H | B / F / S | 24 | 14.0~26.4 | 0.15 | 3200 | 1.61 56.8 | 57.5 0.23 | 38 | ④ |
| AGE09225_24U | B / F / S | 24 | 14.0~26.4 | 0.20 | 3800 | 1.81 64.0 | 64.4 0.26 | 45 | ⑤ |
| AGE09225_24V | B / F / S | 24 | 14.0~26.4 | 0.22 | 4200 | 2.16 76.1 | 87.5 0.35 | 49 | ⑥ |
| AGE09225_48J | B / F / S | 48 | 28.0~56.0 | 0.05 | 2100 | 1.05 37.0 | 23.4 0.09 | 25 | ① |
| AGE09225_48L | B / F / S | 48 | 28.0~56.0 | 0.06 | 2450 | 1.22 43.0 | 31.4 0.13 | 30 | ② |
| AGE09225_48M | B / F / S | 48 | 28.0~56.0 | 0.08 | 2850 | 1.35 47.5 | 41.6 0.17 | 34 | ③ |
| AGE09225_48H | B / F / S | 48 | 28.0~56.0 | 0.10 | 3200 | 1.61 56.8 | 57.5 0.23 | 38 | ④ |

● Drawing & panel out-cuts/ 圖面及出入風口

● Characteristic Curves/ 特性曲線

