

# 92

## AGC series

### 92X92X25mm

#### ●General Specification / 一般規格

- Motor / DC brushless motor
- Material / Frame : plastic(94V-0)  
Impeller : plastic(94V-0)
- Bearing / Ball bearing;FMB
- Weight / 89g
- 馬達 / 直流單向無刷馬達
- 材質 / 框：塑膠(94V-0)  
葉：塑膠(94V-0)
- 軸承 / 滾珠軸承;FMB
- 重量 / 89克



#### ●Specification / 詳細規格 \* 軸承/bearing B: 雙滾珠/ball bearing F:FMB S: 含油軸承/sleeve bearing

Model 機型	Bearing 軸承	Voltage 電壓	Operating Vol. 操作電壓	Current 電流	Speed 轉速	Max. Air Flow 最大風量	Max. Static Pressure 最大風壓	Sound 噪音	P-Q P-Q曲線
P/N	B / S / F	V	V	A	RPM	m <sup>3</sup> /min CFM	Pa In-H <sub>2</sub> O	dBA	No.
AGC09225_12J	B / F	12	7.0~13.2	0.09	2100	1.11 39.2	23.4 0.09	25	①
AGC09225_12L	B / F	12	7.0~13.2	0.11	2450	1.27 44.8	30.9 0.12	30	②
AGC09225_12M	B / F	12	7.0~13.2	0.14	2850	1.48 52.1	42.2 0.17	34	③
AGC09225_12H	B / F	12	7.0~13.2	0.20	3200	1.65 58.3	55.9 0.22	38	④
AGC09225_12U	B / F	12	7.0~13.2	0.30	3800	1.96 69.2	68.6 0.28	45	⑤
AGC09225_12V	B / F	12	7.0~13.2	0.41	4500	2.29 81.0	99.6 0.40	49	⑥
AGC09225_24J	B / F	24	14.0~26.4	0.06	2100	1.11 39.2	23.4 0.09	25	①
AGC09225_24L	B / F	24	14.0~26.4	0.08	2450	1.27 44.8	30.9 0.12	30	②
AGC09225_24M	B / F	24	14.0~26.4	0.13	2850	1.48 52.1	42.2 0.17	34	③
AGC09225_24H	B / F	24	14.0~26.4	0.15	3200	1.65 58.3	55.9 0.22	38	④
AGC09225_24U	B / F	24	14.0~26.4	0.20	3800	1.96 69.2	68.6 0.28	45	⑤
AGC09225_48J	B / F	48	28.0~56.0	0.05	2100	1.11 39.2	23.4 0.09	25	①
AGC09225_48L	B / F	48	28.0~56.0	0.06	2450	1.27 44.8	30.9 0.12	30	②
AGC09225_48M	B / F	48	28.0~56.0	0.08	2850	1.48 52.1	42.2 0.17	34	③
AGC09225_48H	B / F	48	28.0~56.0	0.12	3200	1.65 58.3	55.9 0.22	38	④
AGC09225_48U	B / F	48	28.0~56.0	0.15	3800	1.96 69.2	68.6 0.28	45	⑤

#### ● Drawing & panel out-cuts/ 圖面及出入風口

#### ● Characteristic Curves/ 特性曲線

