

# 92

## AGB series

92X92X38mm

### ●General Specification / 一般規格

- Motor / DC brushless motor
- Material / Frame : plastic(94V-0)
- Impeller : plastic(94V-0)
- Bearing / Ball bearing
- Weight / 200g
- 馬達 / 直流單向無刷馬達
- 材質 / 框：塑膠(94V-0)
- 葉：塑膠(94V-0)
- 軸承 / 滾珠軸承
- 重量 / 200克



### ●Specification / 詳細規格 \* 軸承/bearing B: 雙滾珠/ball bearing F:FMB S: 含油軸承/sleeve bearing

Model 機型	Bearing 軸承	Voltage 電壓	Operating Vol. 操作電壓	Current 電流	Speed 轉速	Max. Air Flow 最大風量	Max. Static Pressure 最大風壓	Sound 噪音	P-Q P-Q曲線
P/N	B / S / F	V	V	A	RPM	m <sup>3</sup> /min CFM	Pa In-H <sub>2</sub> O	dBA	No.
AGB09238B12L	B	12	7.0~13.2	0.50	4300	2.75 97.1	174.8 0.70	52	①
AGB09238B12M	B	12	7.0~13.2	0.90	5000	3.09 109.2	213.2 0.86	58	②
AGB09238B12H	B	12	7.0~13.2	1.20	6000	3.50 123.4	279.7 1.12	64	③
AGB09238B12U	B	12	7.0~13.2	2.50	7000	4.12 145.6	363.3 1.46	67	④
AGB09238B12V	B	12	7.0~13.2	2.95	8000	4.71 166.4	474.5 1.91	72	⑤
AGB09238B24L	B	24	14.0~26.4	0.35	4300	2.75 97.1	174.8 0.70	52	①
AGB09238B24M	B	24	14.0~26.4	0.45	5000	3.09 109.2	213.2 0.86	58	②
AGB09238B24H	B	24	14.0~26.4	0.76	6000	3.50 123.4	279.7 1.12	64	③
AGB09238B24U	B	24	14.0~26.4	1.10	7000	4.12 145.6	363.3 1.46	67	④
AGB09238B24V	B	24	14.0~26.4	1.70	8000	4.71 166.4	474.5 1.91	72	⑤
AGB09238B48L	B	48	28.0~56.0	0.24	4300	2.75 97.1	174.8 0.70	52	①
AGB09238B48M	B	48	28.0~56.0	0.28	5000	3.09 109.2	213.2 0.86	58	②
AGB09238B48H	B	48	28.0~56.0	0.41	6000	3.50 123.4	279.7 1.12	64	③
AGB09238B48U	B	48	28.0~56.0	0.72	7000	4.12 145.6	363.3 1.46	67	④
AGB09238B48V	B	48	28.0~56.0	0.94	8000	4.71 166.4	474.5 1.91	72	⑤

### ● Drawing & panel out-cuts/ 圖面及出入風口

### ● Characteristic Curves/ 特性曲線

