

120 AGC series

120X120X25mm



●General Specification / 一般規格

- Motor / DC brushless motor
- Material / Frame : plastic(94V-0)
- Impeller : plastic(94V-0)
- Bearing / Ball bearing
- Weight / 230g
- 馬達 / 直流單向無刷馬達
- 材質 / 框：塑膠(94V-0)
- 葉：塑膠(94V-0)
- 軸承 / 滾珠軸承
- 重量 / 230克

●Specification / 詳細規格 * 軸承/bearing B: 雙滾珠/ball bearing F:FMB S: 含油承軸/sleeve bearing

Model 機型	Bearing 軸承	Voltage 電壓	Operating Vol. 操作電壓	Current 電流	Speed 轉速	Max. Air Flow 最大風量	Max. Static Pressure 最大風壓	Sound 噪音	P-Q P-Q曲線
P/N	B / S / F	V	V	A	RPM	m ³ /min CFM	Pa In-H ₂ O	dBA	No.
AGC12025B12J	B	12	7.0~13.2	0.20	2100	1.92 67.7	42.2 0.17	35	①
AGC12025B12L	B	12	7.0~13.2	0.30	2500	2.19 77.2	56.9 0.23	39	②
AGC12025B12M	B	12	7.0~13.2	0.48	2800	2.46 86.7	69.6 0.28	42	③
AGC12025B12H	B	12	7.0~13.2	0.50	3400	2.94 103.9	99.0 0.40	47	④
AGC12025B12U	B	12	7.0~13.2	0.62	3700	3.25 114.8	115.7 0.46	50	⑤
AGC12025B12V	B	12	7.0~13.2	0.65	4000	3.43 121.1	127.4 0.51	52	⑥
AGC12025B24J	B	24	14.0~26.4	0.12	2100	1.92 67.7	42.2 0.17	35	①
AGC12025B24L	B	24	14.0~26.4	0.17	2500	2.19 77.2	56.9 0.23	39	②
AGC12025B24M	B	24	14.0~26.4	0.23	2800	2.46 86.7	69.6 0.28	42	③
AGC12025B24H	B	24	14.0~26.4	0.28	3400	2.95 103.9	99.0 0.40	47	④
AGC12025B24U	B	24	14.0~26.4	0.30	3700	3.25 114.8	115.7 0.46	50	⑤
AGC12025B24V	B	24	14.0~26.4	0.40	4000	3.43 121.1	127.4 0.51	52	⑥
AGC12025B48L	B	48	28.0~56.0	0.10	2500	2.19 77.2	56.9 0.23	39	②
AGC12025B48M	B	48	28.0~56.0	0.11	2800	2.46 86.7	69.6 0.28	42	③
AGC12025B48H	B	48	28.0~56.0	0.12	3400	2.95 103.9	99.0 0.40	47	④

● Drawing & panel out-cuts/ 圖面及出入風口

● Characteristic Curves/ 特性曲線

