

# 120 AGE series

## 120X120X38mm



### ●General Specification / 一般規格

- Motor / DC brushless motor
- Material / Frame : plastic(94V-0)  
Impeller : plastic(94V-0)
- Bearing / Ball bearing;sleeve bearing
- Weight / 260g
- 馬達 / 直流單向無刷馬達
- 材質 / 框：塑膠(94V-0)  
葉：塑膠(94V-0)
- 軸承 / 滾珠軸承；含油軸承
- 重量 / 260克

### ●Specification / 詳細規格 \* 軸承/bearing B: 雙滾珠/ball bearing F:FMB S: 含油軸承/sleeve bearing

Model 機型	Bearing 軸承	Voltage 電壓	Operating Vol. 操作電壓	Current 電流	Speed 轉速	Max. Air Flow 最大風量	Max. Static Pressure 最大風壓	Sound 噪音	P-Q P-Q曲線
P/N	B / S / F	V	V	A	RPM	m <sup>3</sup> /min CFM	Pa In-H <sub>2</sub> O	dBA	No.
AGE12038_12M	B / S	12	7.0~13.2	0.18	2300	2.87 101.4	79.7 0.32	38	①
AGE12038_12H	B / S	12	7.0~13.2	0.40	2600	3.25 114.7	102.1 0.41	41	②
AGE12038_12U	B	12	7.0~13.2	0.75	2900	3.49 123.2	112.1 0.45	44	③
AGE12038_12V	B	12	7.0~13.2	0.80	3200	3.85 135.9	134.5 0.54	48	④
AGE12038_12W	B	12	7.0~13.2	1.55	4200	5.05 178.4	234.1 0.94	54	⑤
AGE12038_24L	B / S	24	14.0~26.4	0.14	2300	2.87 101.4	79.7 0.32	38	①
AGE12038_24M	B / S	24	14.0~26.4	0.30	2600	3.25 114.7	102.1 0.41	41	②
AGE12038_24H	B	24	14.0~26.4	0.48	2900	3.49 123.2	112.1 0.45	44	③
AGE12038_24U	B	24	14.0~26.4	0.62	3200	3.85 135.9	134.5 0.54	48	④
AGE12038_24V	B	24	14.0~26.4	0.85	4200	5.05 178.4	234.1 0.94	54	⑤
AGE12038_48I	B / S	48	28.0~56.0	0.10	2300	2.87 101.4	79.7 0.32	38	①
AGE12038_48J	B	48	28.0~56.0	0.14	2600	3.25 114.7	102.1 0.41	41	②
AGE12038_48L	B	48	28.0~56.0	0.25	2900	3.49 123.2	112.1 0.45	44	③
AGE12038_48M	B	48	28.0~56.0	0.30	3200	3.85 135.9	134.5 0.54	48	④
AGE12038_48H	B	48	28.0~56.0	0.48	4200	5.05 178.4	234.1 0.94	54	⑤

### ● Drawing & panel out-cuts/ 圖面及出入風口

### ● Characteristic Curves/ 特性曲線

