

# 120 AGB series

## 120X120X38mm



### ●General Specification / 一般規格

- Motor / DC brushless motor
- Material / Frame : plastic(94V-0)
- Impeller : plastic(94V-0)
- Bearing / Ball bearing
- Weight / 450g
- 馬達 / 直流單向無刷馬達
- 材質 / 框：塑膠(94V-0)
- 葉：塑膠(94V-0)
- 軸承 / 滾珠軸承
- 重量 / 450克



### ●Specification / 詳細規格 \* 軸承/bearing B: 雙滾珠/ball bearing F:FMB S: 含油軸承/sleeve bearing

Model 機型	Bearing 軸承	Voltage 電壓	Operating Vol. 操作電壓	Current 電流	Speed 轉速	Max. Air Flow 最大風量	Max. Static Pressure 最大風壓	Sound 噪音	P-Q P-Q曲線
P/N	B / S / F	V	V	A	RPM	m <sup>3</sup> /min CFM	Pa In-H <sub>2</sub> O	dBA	No.
AGB12038B12L	B	12	7.0~13.2	2.00	4000	4.85 171.4	174.5 0.70	60	①
AGB12038B12M	B	12	7.0~13.2	2.50	4800	5.84 206.3	256.8 1.03	65	②
AGB12038B12H	B	12	7.0~13.2	3.88	5500	6.65 234.7	337.2 1.35	69	③
AGB12038B24L	B	24	14.0~26.4	1.30	4000	4.85 171.4	174.5 0.70	60	①
AGB12038B24M	B	24	14.0~26.4	1.80	4800	5.84 206.3	256.8 1.03	65	②
AGB12038B24H	B	24	14.0~26.4	2.50	5500	6.65 234.7	337.2 1.35	69	③
AGB12038B24U	B	24	14.0~26.4	2.72	6200	7.53 265.8	433.3 1.74	72	④
AGB12038B48L	B	48	28.0~56.0	0.60	4000	4.85 171.4	174.5 0.70	60	①
AGB12038B48M	B	48	28.0~56.0	0.90	4800	5.84 206.3	256.8 1.03	65	②
AGB12038B48H	B	48	28.0~56.0	1.20	5500	6.65 234.7	337.2 1.35	69	③
AGB12038B48U	B	48	28.0~56.0	1.30	6200	7.53 265.8	433.3 1.74	72	④

### ● Drawing & panel out-cuts/ 圖面及出入風口

### ● Characteristic Curves/ 特性曲線

